

PAINTED NUBBY™

Square Lay-in & Tegular
medium texture



Painted Nubby with Prelude® 15/16" suspension system (Pg. 259)


KEY SELECTION ATTRIBUTES

- Outstanding acoustical performance; both Articulation Class (180-190) and NRC (0.85-0.95)
- Fiberglass substrate will resist mold/mildew and bacterial growth
- 30-Year Limited System Warranty against visible sag, mold/mildew, and bacterial growth

TYPICAL APPLICATIONS

- Open plan offices
- Areas requiring superior acoustics and sag resistance

DETAIL



1. Painted Nubby Tegular
2. Painted Nubby Tegular with Silhouette® 9/16" suspension system 1/4" reveal

COLOR



PAINTED NUBBY™

Square Lay-in & Tegular

medium texture

UP TO **71%** RECYCLED CONTENT

LEED®

- acoustics
- energy
- daylight & views
- indoor air quality
- renewable materials
- recycled content
- waste mgmt
- local* materials

Calculate LEED contribution at armstrong.com/greengenie *LOCATION DEPENDENT

VISUAL SELECTION

PERFORMANCE

Dots represent high level of performance.

Edge Profile	Susp. Dwg. Pgs. 273-277 armstrong.com/catdwgs	Item No.	Dimensions (Inches)	Acoustics		Fire Rating	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Durability	Recycled Content*	Recycle Program	Warranty*	
				NRC	CAC										
PAINTED NUBBY Square Lay-in															
15/16" Square Lay-in	1	3102	24 x 24 x 1"	0.95	N/A	190	Class A	0.84	•	•	–	Std	High	–	30
	1	3101	24 x 48 x 3/4"	0.85	N/A	180	Class A	0.84	•	•	–	Std	High	–	30
	1	3103	24 x 48 x 1"	0.95	N/A	190	Class A	0.84	•	•	–	Std	High	–	30
	1	3104	48 x 96 x 1"	0.95	N/A	190	Class A	0.84	•	•	–	Std	High	–	30
	1	Other Sizes	W: 4" - 48" / L: 4" - 120" 3/4" or 1" Thick	0.95	N/A	190	Class A	0.84	•	•	–	Std	High	–	30
PAINTED NUBBY Tegular															
15/16" Square Tegular	8	3200	24 x 24 x 1"	0.95	N/A	190	Class A	0.84	•	•	–	Std	High	–	30
9/16" Square Tegular	26, 43, 47, 51, 55, 59	3201	24 x 24 x 1"	0.95	N/A	190	Class A	0.84	•	•	–	Std	High	–	30
	26, 43, 47, 51, 55, 59	Other Sizes	W: 4" - 48" / L: 4" - 120" 3/4" or 1" Thick	0.95	N/A	190	Class A	0.84	•	•	–	Std	High	–	30

SUSPENSION SYSTEMS



PHYSICAL DATA

Material
Fiberglass with fabric facing

Surface Finish
Factory-applied latex paint

Fire Performance
ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)

ASTM E1264 Classification
Type XII, Form 2, Pattern E
Fire Class A

Sag Resistance
HumiGuard® Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

Anti Mold/Mildew & Bacteria
Fiberglass substrate is inherently resistant to the growth of mold, mildew, and bacteria.

High Recycled Content*
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Acoustical Details
A CAC value of 37 can be achieved by backloading fiberglass products with Item 769 or 770.

Insulation Value
3101 – R Factor - 3.0 (BTU units)
R Factor - 0.53 (Watts units)
3102, 3103, 3200, 3201 – R Factor - 4.0 (BTU units)
R Factor - 0.70 (Watts units)

30-Year Performance Guarantee & Warranty†
When installed with Armstrong Suspension System. Details at armstrong.com/warranty

Weight; Square Feet/Carton
3101 – 0.44 lbs/SF; 128 SF/ctn
3102, 3103 – 0.46 lbs/SF; 96 SF/ctn
3104 – 0.46 lbs/SF; 128 SF/ctn
3200, 3201 – 0.55 lbs/SF; 96 SF/ctn

Minimum Order Quantity
1 carton, excludes other sizes

Metric Items Available
3102M, 3101M, 3103M, 3200M, 3201M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.



FIBERGLASS