

# FISSURED™

## Square Lay-in & Tegular

medium texture

UP TO **41%** RECYCLED CONTENT

LEED®

- acoustics
- energy
- daylight & views
- indoor air quality
- renewable materials
- recycled content
- waste mgmt
- local\* materials



Calculate LEED contribution at [armstrong.com/greengenie](http://armstrong.com/greengenie)

\*LOCATION DEPENDENT



Fissured Angled Tegular with Prelude® 15/16" suspension system (Pg. 259)

### KEY SELECTION ATTRIBUTES

- Economical
- Directional fissured image

### TYPICAL APPLICATIONS

- Utility rooms
- Discount stores

### COLOR



White


### VISUAL SELECTION

### PERFORMANCE

Dots represent high level of performance.

Edge Profile	Suspension Detail Dwg. Pgs. 273-277	Item No.	Dimensions (Inches)	Acoustics		Fire Rating	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	Warranty
				NRC	CAC									
<b>FISSURED Square Lay-in</b>				UL Classified										
	1	<b>756</b>	24 x 24 x 5/8"	0.55	30	Class A	0.81	-	Std	•	Std	Std	•	1
	1	<b>896</b>	24 x 24 x 5/8"	0.55	35	Fire Guard	0.81	-	Std	•	Std	Std	•	1
	1	<b>755</b>	24 x 48 x 5/8"	0.55	30	Class A	0.81	-	Std	•	Std	Std	•	1
	1	<b>895</b>	24 x 48 x 5/8"	0.55	35	Fire Guard	0.81	-	Std	•	Std	Std	•	1
	1	<b>Other Sizes</b>	W: 12" - 30" / L: 18" - 72" 5/8" thick	0.55	35	Class A	0.81	-	Std	•	Std	Std	•	1
<b>FISSURED Tegular</b>														
	11	<b>705</b>	24 x 24 x 5/8"	0.55	30	Class A	0.81	-	Std	•	Std	Std	•	1
	11	<b>815</b>	24 x 24 x 5/8"	0.55	35	Fire Guard	0.81	-	Std	•	Std	Std	•	1
	11	<b>Other Sizes</b>	W: 12" - 30" / L: 18" - 72" 5/8" thick	0.55	35	Class A	0.81	-	Std	•	Std	Std	•	1

### SUSPENSION SYSTEMS



### PHYSICAL DATA

**Material**  
Wet-formed mineral fiber

**Surface Finish**  
Factory-applied latex paint

**Fire Performance**  
ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled) Fire Guard™: A fire resistive ceiling when used in applicable UL assemblies

**ASTM E1264 Classification**  
Type III, Form 2, Pattern C D  
Fire Class A

**VOC Emissions**  
Third party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010. This standard is the guideline for low emissions in LEED, CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

**Insulation Value**  
755, 756, 895, 896 –  
R Factor – 1.5 (BTU units)  
R Factor – 0.26 (Watts units)  
705, 815 –  
R Factor – 1.6 (BTU units)  
R Factor – 0.28 (Watts units)

**Weight: Square Feet/Carton**  
705 – 0.69 lbs/SF; 64 SF/ctn  
755 – 0.66 lbs/SF; 96 SF/ctn  
756 – 0.67 lbs/SF; 64 SF/ctn  
815 – 1.08 lbs/SF; 48 SF/ctn  
895, 896 – 1.09 lbs/SF; 64 SF/ctn

**Minimum Order Quantity**  
1 carton, excludes other sizes

**Metric Items Available**  
756M, 896M, 755M, 895M, 705M  
Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.



MINERAL FIBER