



TUNDRA®

Square Lay-in & Tegular
medium texture

UP TO **35%** RECYCLED CONTENT

LEED®

- acoustics
- energy
- daylight & views
- indoor air quality
- renewable materials
- recycled content
- waste mgmt
- local* materials

Calculate LEED contribution at armstrong.com/greengenie

*LOCATION DEPENDENT



Tundra with Suprafine® 9/16" suspension system (Pg. 266)

KEY SELECTION ATTRIBUTES

- Durable
 - Impact-resistant
 - Scratch-resistant
- 30-Year Limited System Warranty against visible sag, mold/mildew, and bacterial growth

TYPICAL APPLICATIONS

- Offices
- Schools
- Corridors

COLOR




VISUAL SELECTION

PERFORMANCE

Dots represent high level of performance.

Edge Profile	Susp. Dwg. Pgs. 273-277 armstrong.com/catdwgs	Item No.	Dimensions (Inches)	Acoustics		Fire Rating	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Durability		Recycled Content	Recycle Program	Warranty*
				NRC	CAC						Impact	Scratch			
TUNDRA															
UL Classified															
15/16" Square Lay-in	1	301	24 x 24 x 5/8" □	0.50	33	Class A	0.87 ●	●	●	–	●	●	Std	●	30
	1	302	24 x 48 x 5/8" □	0.50	35	Class A	0.87 ●	●	●	–	●	●	Std	●	30
	1	Other Sizes	W: 24" / L: 24" - 48" 5/8" Thick	0.50	35	Class A	0.87 ●	●	●	–	●	●	Std	●	30
15/16" Beveled Tegular	15	303	24 x 24 x 5/8" □	0.50	33	Class A	0.87 ●	●	●	–	●	●	Std	●	30
	15	305	24 x 48 x 5/8" □	0.50	35	Class A	0.87 ●	●	●	–	●	●	Std	●	30
	15	Other Sizes	W: 24" / L: 24" - 48" 5/8" Thick	0.50	35	Class A	0.87 ●	●	●	–	●	●	Std	●	30
9/16" Beveled Tegular	29, 43, 47, 51, 55, 59	304	24 x 24 x 5/8" □	0.50	33	Class A	0.87 ●	●	●	–	●	●	Std	●	30
	29, 43, 47, 51, 55, 59	Other Sizes	W: 24" / L: 24" - 48" 5/8" Thick	0.50	33	Class A	0.87 ●	●	●	–	●	●	Std	●	30

SUSPENSION SYSTEMS



PHYSICAL DATA

Material
Wet-formed high density mineral fiber

Surface Finish
Factory-applied latex paint with scuff-resistant spatter coat

Fire Performance
ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled) Fire Guard™: A fire resistive ceiling when used in applicable UL assemblies



ASTM E1264 Classification
Type III, Form 2, Pattern C E
Fire Class A

Sag Resistance
HumiGuard® Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

Anti Mold/Mildew & Bacteria
BioBlock® Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

Insulation Value
R Factor – 1.7 (BTU units)
R Factor – 0.30 (Watts units)

30-Year Performance Guarantee & Warranty*
When installed with Armstrong Suspension System. Details at armstrong.com/warranty

Weight; Square Feet/Carton
301, 302, 305 – 1.09 lbs/SF; 64 SF/ctn
303, 304 – 1.10 lbs/SF; 48 SF/ctn

Minimum Order Quantity
1 carton, excludes other sizes

Metric Items Available
302M, 303M, 305M, 304M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

TechLineSM / 1 877 ARMSTRONG
armstrong.com/commceilings
(search: tundra)
BPCS-3038-813

LEED® is a registered trademark of the U.S. Green Building Council
All other trademarks used herein are the property of AWI Licensing Company and/or its affiliates © 2013 AWI Licensing Company
Printed in the United States of America

